

**Product Information:**

# Universal Adhesive 300

**The well known yellow tube, for most applications**

**General description and typical applications:**

*Universal Adhesive 300 is a fast curing all-round adhesive, which gives a translucent joint. Suitable for bonding of wood, china, cork, paper, cardboard and some textiles, plastic types etc.*

*The well known yellow tube, which have been the favourite Danish universal adhesive for more than 80 years.*



*Universal Adhesive 300 is a fast curing all-round adhesive, which gives a translucent joint. Suitable for bonding of wood, china, cork, paper, cardboard and some textiles, plastic types etc.*

**Physical / chemical properties:**

**Adhesive:**

- Type: Solvent based cellulose adhesive
- Colour: Translucent
- Consistency: Liquid
- Shelf life: Minimum 2 years in closed packing if stored cool and dry.
- Packaging:

Item no.	Size
1100	40 ml tube (12pcs pack)

**Joint:**

- Colour: Translucent
- Resistance:
  - Temperature: The adhesive is resistant to temperatures up to approx. 70 °C, depending on strength requirements. The adhesive is thermoplastic (i.e. strength is reduced with increasing temperature).

Water: Good.



## Directions for use:

### Preparation:

*The surfaces must be clean, dry and free of oil, grease, dust, and loose particles.*

*When bonding metals, plastic types etc, a sanding of the surfaces will improve bonding strength.*

*It is always recommended to carry out an adhesive test on the materials which should be bonded.*

*When bonding textiles, leather etc., there is a risk of discolouration because of the organic solvents in the adhesive. Always carry out a test before using the adhesive.*

### Application:

*The adhesive is applied on one or both surfaces. The surfaces are pressed together within max. 3 minutes, while the adhesive is still wet.*

*The surfaces must be pressed together while the adhesive is curing, approx. 15 minutes at 20 °C.*

### Cleaning:

*Uncured adhesive can be cleaned with acetone.*

## Health and safety:

### Hazard symbol:

*Xi, irritant*

*F, highly flammable*

### Risk and safety phrases:

*Irritating to eyes.*

*Toxic to aquatic organisms; may cause long-term adverse effects in the aquatic environment. Repeated exposure may cause skin dryness or cracking.*

*Vapours may cause drowsiness and dizziness.*

*Keep out of the reach of children.*

*Keep away from sources of ignition. No smoking.*

*In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.*

*If swallowed, seek medical advice immediately and show this container or label.*

*For further information, please refer to safety datasheet.*

*The information and data contained in this Product Information sheet are based on extensive laboratory testing and our practical experiences, and are meant for helping the user to find optimum working methods. As the conditions at the user are beyond our control, we make no warranties concerning the results, achieved by the products. The information's in this Product Information sheet are typical values, intended as a guideline. They should not be regarded as product specifications. Please also refer to our standard sales conditions and terms of delivery.*

**DANA LIM A/S - KØBENHAVNSVEJ 220 - DK-4600 KØGE – DENMARK – INFO@DANALIM.DK  
PH. (+45) 56 64 00 70 - TELEFAX (+45) 56 64 00 90 - TECHNICAL SERVICE PH. (+45) 56 64 00 75**